

Flush Mount Series DC Light Fixture w/ 5W or 12W Lamp



Flush Mount Series

FM-48DC-5-WH

FM-125DC-5-WH

FM-125DC-12-WH

FM-125DC-12-WH

APPLICATIONS: designed for non-insulated areas* and damp locations

5 Watt 48DC or 125DC LED

- Lamp Power: 5 Watts @ 48DC or 125DC
- Light Output: 420 Lumens
- Power Factor: >90 Base: A19
- Lamp Size: 2 1/4" x 3 3/4"
- Beam Angle: 180°
- Color Temp: 5000K
- Op. Temp: -4°F to + 113°F
- Life Span: 20,000 Hours
- Certification: CE & FCC
- Warranty: 3 Year replacement

12 Watt 48DC or 125DC LED

- Lamp Power: 12 Watts @ 48DC or 125DC
- Light Output: 800 Lumens
- Power Factor: >90
- Base: A19
- Bulb Size: 2 1/4" x 5 5/16"
- Beam Angle: 180°
- Color Temp: 5000K
- Op. Temp: -4°F to + 113°F

- Life Span: 20,000 Hours
- Certification: CE & FCC
- Warranty: 3 Year replacement

FM-1LED-48DC-5-WH

FM-1LED-125DC-12-WH

- FM-1LED: One (1) LED bulb
- 48DC or 125DC: Voltage Input
- 5 or 12: 5 or 12 Watt Bulb
- WH: White Painted Steel

SPECIFICATIONS:

- 22ga. White Painted steel
- 12"W x 12"L x 5 ½"H Nominal Size
- Crystal Tempered Glass Diffuser
- Suitable for damp Locations
- UL Listed & CSA Certified
- Adjustable housing up to 1" Thick Ceilings
- Includes 5 Knockouts - Bar hangers for easy installation

Notes:

1. When ordering please indicate project.
2. * Indicates a 3" insulation clearance around Light Fixture.

Marshall DC Lighting
329 W Lone Cactus Drive Suite 1 Phoenix, AZ 85027

www.marshalldc.com

info@dclightfixtures.com

602-777-0028