

Hi-Temp Industrial “V” Series 3 LED Light Fixture (AC/DC combo)



AC/DC Combination 48” High Temperature Series Fluorescent Light Fixture

Construction: High quality aluminum body; End caps vented to keep unit cool in a wide range of operating temperatures. UL Listed for damp and high temperature locations. Includes two (2) AC tubes and one (1) DC tube.

T8IH-3LED-120/277AC(2L)-24DC(1L)-20-WH

T8IH-3LED-120/277AC(2L)-48DC(1L)-20-WH

T8IH-3LED-120/277AC(2L)-125DC(1L)-20-WH

- T8: Lamp Type
- IH: High Temperature
- 3LED: Three (3) T8 Tubes
- 120/277AC: Alternating Current (AC)
- (2L): Two (2) AC LED Tubes
- 24DC, 48DC or 125DC: DC Input Voltage
- (1L): One (1) LED Tube @ 48DC or 125DC
- 20: 20Watt Tube
- WH: White reflector

Dimensions: 48” x 10 ¾” x 3 1/8”

Two (2) Outer Lamps @ 120/277AC & One (1) Inner lamp 24DC, 48DC or 125DC

T8 18 Watt 120/277AC LED Tube

- Input Voltage: 120/277AC
- Frequency: 50>60Hz
- Power factor: >0.90
- Size: 1” x 48”
- Power: 18Watts
- Color: Frosted @ 5000K
- Lumens: 1500

- PC Lens: Clear
- Beam Angle: 120°
- Life Expectancy: 50,00 Hrs.
- Certification: UL & CUL
- Warranty: 3 Years

T8 20 Watt 24DC, 48DC or 125DC LED Tube

- Input Voltage: 24DC, 48DC or 125DC
- Power Factor: > 90
- Size: 1" x 48"
- Power: 20W
- Lumens: 1800
- Color: 4000K
- Color Rendering Index: > 80
- PC Lens: Milky
- Beam Angle: 160°
- Lamp Life Expectancy: 50,000 Hours
- Operating Temperature: -4F to +150 F
- Warranty: 3 Years

Notes:

1. When ordering or requesting a Proposal, please indicate project.
2. All fixtures are UL & CUL listed and manufactured in the U.S.A.
3. Wire gage optional

Marshall DC Lighting
329 W Lone Cactus Drive Suite 1 Phoenix, AZ 85027

www.marshalldc.com

info@dclightfixtures.com

602-777-0028